IBM 000-056

Rational BuildForge v7.1
Version: 5.0

QUESTION NO: 1

How do Build Forge Eclipse IDE plug-ins enable Pre-Flight builds?

A. through configuration of the Eclipse Build Forge Perspective
B. through configuration of the Eclipse Build Forge Project Artifacts properties
C. by configuring Eclipse to use Dynamic Views for integration builds
D. through build status reporting via the Eclipse Build Forge Frequency Plug-In

Answer: B
Explanation:

QUESTION NO: 2

What should you do to allocate more console resources for running jobs?

A. adjust the Active Server Refresh Interval to a higher time value than the default
B. adjust the Database Size Threshold to a value smaller than the default
C. set the Hard Run Limit
D. increase the value for Server Retries

Answer: A
Explanation:

QUESTION NO: 3

What can developers use to start Build Forge projects and view job results from within their IDE?

A. the Build Forge IDE
B. the TFS plug-in
C. the Build Forge Eclipse perspective
D. an iPhone running Firefox

Answer: C
Explanation:

QUESTION NO: 4

What do Build Forge Performance Reports require?

A. installation of BIRT
B. template customization for each console installation
C. correct permissions to view the reports
D. at least 1GB of additional RAM

Answer: C
Explanation:

QUESTION NO: 5

What can permissions in Build Forge be assigned to?

A. access groups
B. users and data objects
C. users and access groups
D. only users and groups

Answer: A
Explanation:

QUESTION NO: 6

Which projects can users view?

A. projects that have been assigned to their team
B. projects that are part of their permission list
C. projects for which they are members of the access group
D. projects that have not set the property to idden?projects that have not set the property to
?idden

Answer: C
Explanation:

QUESTION NO: 7

What should be used to ensure a high priority job will have needed slots on a server?

A. BF_LOADRATIO
B. BF_JOBS
C. BF_RESERVE
D. BF_EXCLUSIVE

Answer: D
Explanation:

QUESTION NO: 8

You want to configure the Build Forge Management Console to use an alternative port. Where should you change the port settings to accomplish this?

A. in the buildforge.conf files
B. in the Apache httpd.conf file
C. in the Tomcat catalina.properties file
D. in the Build Forge webroot init.php file

Answer: B
Explanation:

QUESTION NO: 9

Which statement is true about restarting a failed job?

A. Changes to the project environment can be made available.
B. Changes to the build tag can be made.
C. Changes to the project steps can be made available.
D. The entire project is rerun.

Answer: C
Explanation:

QUESTION NO: 10

The FLEXlm license server is required for which Build Forge editions? (Select two.)

A. Enterprise Plus