

IBM 000-733

000-733 DB2 9 Application Developer

Practice Test

Version 1.1

QUESTION NO: 1

A .NET application executes a SQL request invoking the DB2Command.ExecuteReader method and a syntax error exception is thrown. Which of the following properties contains the SQLCode for this syntax error?

- A. DB2Error.SQLCode
- B. SQLError.SQLCode
- C. DB2Exception.SQLCode
- D. SQLException.SQLCode

Answer: A

QUESTION NO: 2

Given the following table definition:

```
CREATE TABLE staff (  
id SMALLINT NOT NULL,  
name VARCHAR(9),  
dept SMALLINT,  
job CHAR(5))
```

Assuming that the following statements execute successfully:

```
Dim cmdStaff As DB2Command = cnDb2.CreateCommand()  
cmdStaff.CommandText = "SELECT name FROM staff WHERE (job = @job)"
```

Which of the following is the correct way to provide a value for the parameter marker used?

- A. cmdStaff.Parameters.Add("@job", "Mgr", CType(5, Char))
- B. cmdStaff.Parameters.Add("@job", "Mgr", DB2Type.Char, 5)
- C. cmdStaff.Parameters.Add(New DB2Parameter("@job", CType(5, Char))
cmdStaff.Parameters("@job").Value = "Mgr"
- D. cmdStaff.Parameters.Add(New DB2Parameter("@job", DB2Type.Char, 5)
cmdStaff.Parameters("@job").Value = "Mgr"

Answer: D

QUESTION NO: 3

If the following code is executed in the order shown:

```
conDB2 As DB2Connection
conDB2.ConnectionString = "Database=samplelx;UID=db2user;PWD=db2pwd;"
conDB2.Open()
```

Which of the following statements is correct?

- A. An exception is thrown because the server name has not been specified.
- B. An exception is thrown because the server name and the port have not been specified.
- C. The execution is successful provided the host name SAMPLEX has been previously defined in the local hosts table.
- D. The execution is successful provided the database alias SAMPLEX has been previously defined in the local database catalog.

Answer: D

QUESTION NO: 4

Which of the following is the DB2 Data Provider for the .NET class that requires a database connection to be open?

- A. DB2DataSet
- B. DB2RecordSet
- C. DB2DataReader
- D. DB2DataAdapter

Answer: C

QUESTION NO: 5

Which of the following ADO .NET providers is supported by IBM DB2 Add-ins for Visual Studio?

- A. OLE DB .NET Data Provider
- B. DB2 Data Provider for .NET
- C. ODBC Data Provider for .NET
- D. DB2 for i5/OS .NET Provider

Answer: B

QUESTION NO: 6

Two OLTP applications run concurrently but frequent locking occurs which requires a fix to be applied. Application A inserts rows into the table T1. Application B submits several queries against the table with a Cursor Stability isolation level. What would be the best course of action to improve the system's concurrency and performance?

- A. Application B should be changed to access a view of table T1.
- B. Application B should be changed to a Read Stability isolation level.
- C. Application A should be changed to perform a commit after each INSERT operation.
- D. Application A should be changed to include the NOT WITH HOLD clause on each INSERT operation.

Answer: C

QUESTION NO: 7

Parameter markers are NOT permitted for which of the following statements?

- A. CALL
- B. DELETE
- C. EXECUTE IMMEDIATE
- D. SET CURRENT SQLID

Answer: C

QUESTION NO: 8

Given following table:

```
EMP
EMPNO NAME DEPTNO SALARY
=====
0010 JOSH D95 30000
0020 JENNA D98 25000
0030 DYLAN D95 10000
0040 TRACY D90 33000
```

and the following trigger definition:

```
CREATE TRIGGER track_chgs
AFTER UPDATE OF salary, name, empno ON emp
REFERENCING NEW_TABLE AS ntable
```

```
FOR EACH STATEMENT MODE DB2SQL
BEGIN ATOMIC
INSERT INTO changes
SELECT empno, CURRENT_TIMESTAMP FROM ntable;
END;
```

After executing the following SQL statements:

```
DELETE FROM changes;
UPDATE emp SET deptno = 'D98' WHERE deptno = 'D95';
INSERT INTO emp VALUES('0050', 'KEN', 'D90', 35000);
UPDATE emp SET salary = salary - 500 WHERE salary > 35000;
UPDATE emp SET salary = salary + 1000 WHERE salary <= 25000;
What value will be returned by this query?
SELECT count(*) FROM changes
```

- A. 2
- B. 3
- C. 4
- D. 6

Answer: A

QUESTION NO: 9

Given the following table and view definitions:

```
CREATE TABLE city (
cityid INT GENERATED ALWAYS AS IDENTITY ,
city_name CHAR(10),
state_code CHAR(2) CHECK(state_code IN ('CA','IL','NY','OH','TX'));
CREATE VIEW city_view AS (
SELECT city_name||','||state_code AS fullname FROM city
```

```
WHERE state_code NOT IN ('OH','IL'));
```

and the following trigger definition:

```
CREATE TRIGGER city_viewInput
INSTEAD OF INSERT ON city_view
REFERENCING NEW AS n
FOR EACH ROW MODE DB2SQL
```

```
BEGIN ATOMIC
DECLARE delim INT;
SET delim = LOCATE(',', n.fullname);
INSERT INTO city(city_name,state_code)
VALUES(SUBSTR(n.fullname, 1, delim - 1), SUBSTR(n.fullname, delim + 1, 2));
END;
```

If the following SQL statements are executed:

```
INSERT INTO city VALUES(DEFAULT,'San Jose','CA') ;
INSERT INTO city_view VALUES('Chicago,IL');
INSERT INTO city VALUES(DEFAULT,'Detroit','MI');
INSERT INTO city VALUES(DEFAULT,'Austin','TX');
INSERT INTO city_view VALUES('Denver,CO');
```

How many rows will be returned by the following query:

```
SELECT * FROM city
```

- A. 1
- B. 2
- C. 3
- D. 4

Answer: C

QUESTION NO: 10

An application running against a DB2 for AIX database needs to execute the following query:

```
SELECT t2.c2, t1.c3 FROM t1 INNER JOIN t2 ON t1.c1 = t2.c1
```

If table T1 resides in the DB2 for AIX database and table T2 resides in a DB2 for i5/OS database, which of the following DB2 object types must the identifier T2 represent in order for this SQL statement to run successfully?

- A. ALIAS
- B. NICKNAME
- C. SERVER TABLE
- D. TABLE WRAPPER

Answer: B

QUESTION NO: 11

After executing the following SQL statements:

```
CREATE TABLE tab1 (
col1 INT ,
col2 CHAR(1),
PRIMARY KEY(col1));
CREATE TABLE tab2 (
col1 INT ,
col2 CHAR(1),
FOREIGN KEY (col1) REFERENCES tab1(col1)
ON DELETE CASCADE
ON UPDATE NO ACTION );
INSERT INTO tab1 VALUES(1, 'A');
INSERT INTO tab1 VALUES(2, 'B');
INSERT INTO tab2 VALUES(3, 'A');
INSERT INTO tab2 VALUES(2, 'B');
UPDATE tab1 SET col1 = col1 + 1;
DELETE FROM tab1 WHERE col2 = 'B';
```

What values will be returned by the following SQL query?

```
SELECT col1, col2 FROM tab1 A.COL1 COL2 ===== 2 'B'
```

A. COL1 COL2

```
=====
```

2 'B'

B. COL1 COL2

```
=====
```

2 'A'

C. COL1 COL2

```
=====
```

1 'A'

2 'B'

D. COL1 COL2

```
=====
```

2 'A'

3 'B'

Answer: B

QUESTION NO: 12

Which of the following SQL statements demonstrates the correct usage of a parameter marker?

- A. SELECT ? FROM SYSCAT.TABLES
- B. SELECT [] FROM SYSCAT.TABLES
- C. SELECT CAST(? AS INTEGER) FROM SYSCAT.TABLES
- D. SELECT CAST([] AS INTEGER) FROM SYSCAT.TABLES

Answer: C

QUESTION NO: 13

An SQL procedure has been developed with several inline SQL PL statements encapsulated in a dynamic compound SQL statement. The procedure had been tested and performed well. After making a change to the last SQL statement the procedure not only failed to complete, but did not produce output from any statements which were not modified. What is the best explanation for this behavior?

- A. The dynamic compound SQL is atomic.
- B. The procedure doesn't have any savepoints.
- C. The procedure has not been correctly re-cataloged.
- D. The dynamic compound SQL individual statements are logically dependent on each other.

Answer: A

QUESTION NO: 14

Which of the following is a characteristic of an application that uses a Distributed Unit of Work (DUOW)?

- A. A single transaction can only read and/or modify data stored on one database server.
- B. Multiple transactions can only read and/or modify data stored on one database server.
- C. A single transaction can read and/or modify data stored across multiple database servers.
- D. Multiple transactions can read and/or modify data stored on multiple database servers provided each transaction only accesses a single server.

Answer: C

QUESTION NO: 15

Table EMPLOYEE contains the following rows:

```
EMPNO  FIRSTNME  LASTNAME  WORKDEPT
-----  -
```

```
000010  CHRISTINE  HAAS  A00
```

```
000020  MICHAEL  THOMPSON  B01
```

```
000030  SALLY  KWAN  C01
```

The isolation level for Application 1 is set to CS and autocommit is disabled. The isolation level for Application 2 is set to CS and the autocommit is enabled.

The following statements are executed in sequence:

Application 1:

```
-----
```

```
DECLARE c1 CURSOR FOR SELECT * FROM employee ORDER BY empno
```

```
OPEN C1
```

```
FETCH C1
```

```
FETCH C1
```

Application 2:

```
-----
```

```
UPDATE employee SET lastname = 'MILLFORD' WHERE empno = '000020'
```

Which of the following statements is correct?

- A. The UPDATE succeeds because Application 2 runs with autocommit enabled so no row level locks are necessary for the update.
- B. The UPDATE succeeds because Application 1 holds a row level lock that is compatible with the lock required by Application 2.
- C. The UPDATE fails because Application 1 holds a row level read lock that is in conflict with the lock required by Application 2.C.
- D. The UPDATE fails because the row level locks held by Application 1 have been escalated to table lock so updates by other connections are disallowed.

Answer: B

QUESTION NO: 16

Which of the following is a SQL stored procedure which will return a resultset containing ID, NAME, DEPT and JOB values out of the STAFF table?

A. CREATE PROCEDUREresult_set()

LANGUAGE SQL

BEGIN

SELECT id, name, dept, job

FROM staff;

END

B. CREATE PROCEDUREresult_set

LANGUAGE SQL

RESULT SETS 1

BEGIN

SELECT id, name, dept, job

FROM staff;

END

C. CREATE PROCEDUREresult_set

RESULT SETS 1

BEGIN

DECLARE c1 CURSOR FOR

SELECT id, name, dept, job

FROM staff;

OPEN C1;

END

D. CREATE PROCEDUREresult_set()

LANGUAGE SQL

RESULT SETS 1

BEGIN

DECLARE c1 CURSOR WITH RETURN FOR

SELECT id, name, dept, job

FROM staff;

OPEN c1;

END

Answer: D

QUESTION NO: 17

After installing the DB2 Express-C 9 it was discovered that the Development Workbench was not available. What was the reason for that?

A. It must be installed separately.

B. It is not supported with DB2 Express-C 9.

C. Since it is a licensed tool, it must be purchased from IBM.