

**Oracle 1z0-007**

**Introduction to Oracle9i: SQL**

**Version: 22.0**

**QUESTION NO: 1**

Examine the data in the EMPLOYEES and DEPARTMENTS tables.

**EMPLOYEES**

LAST_NAME	DEPARTMENT_ID	SALARY
Getz	10	3000
Davis	20	1500
King	20	2200
Davis	30	5000
Kochhar		5000

**DEPARTMENTS**

DEPARTMENT_ID	DEPARTMENT_NAME
10	Sales
20	Marketing
30	Accounts
40	Administration

You want to retrieve all employees, whether or not they have matching departments in the departments table. Which query would you use?

- A.** SELECT last\_name, department\_name  
FROM employees ,departments(+);
- B.** SELECT last\_name, department\_name  
FROM employees JOIN departments (+);
- C.** SELECT last\_name, department\_name  
FROM employees(+) e JOIN departments d  
ON (e.department\_id = d.department\_id);
- D.** SELECT last\_name, department\_name  
FROM employees e  
RIGHT OUTER JOIN departments d ON (e.department\_id = d.department\_id);
- E.** SELECT last\_name, department\_name  
FROM employees(+) , departments  
ON (e.department\_id = d.department\_id);
- F.** SELECT last\_name, department\_name  
FROM employees e LEFT OUTER  
JOIN departments d ON (e.department\_id = d.department\_id);

**Answer: F**

**Explanation:**

Answer F is correct. This query shows correct syntax to retrieve all employees, whether or not they have matching departments in the department table. Oracle9i extends its compliance with ANSI/ISO by supporting that standard's requirements for outer join syntax and semantics.

**Incorrect Answers**

A: This query uses "+" to create outer join as it was in Oracle8i, but it requires also usage of WHERE clause in SELECT statement.

B: The JOIN clause cannot be used with in conjunction with "+": syntax is incorrect.

C: The JOIN clause cannot be used with in conjunction with "+": syntax is incorrect.

D: This statement requires LEFT OUTER JOIN, not RIGHT OUTER JOIN.

E: This query uses incorrect syntax with "+" and ON to create outer join.

OCP Introduction to Oracle 9i: SQL Exam Guide, Jason Couchman, p. 112-114

Chapter 3: Advanced Data Selection in Oracle

**QUESTION NO: 2**

Examine the structure of the EMPLOYEES table:

EMPLOYEE\_ID NUMBER Primary Key

FIRST\_NAME VARCHAR2(25)

LAST\_NAME VARCHAR2(25)

Which three statements inserts a row into the table? (Choose three)

**A.** INSERT INTO employees

VALUES ( NULL, 'John','Smith');

**B.** INSERT INTO employees( first\_name, last\_name)

VALUES('John','Smith');

**C.** INSERT INTO employees

VALUES ('1000','John',NULL);

**D.** INSERT INTO employees(first\_name,last\_name, employee\_id)

VALUES ( 1000, 'John','Smith');

**E.** INSERT INTO employees (employee\_id)

VALUES (1000);

**F.** INSERT INTO employees (employee\_id, first\_name,last\_name)

VALUES ( 1000, 'John', '' );

**Answer: C,E,F**

**Explanation:**

Since EMPLOYEE\_ID column is used as primary key, it cannot be NULL, so only INSERT statements in C, E and F are correct. You can insert the row with NULL LAST\_NAME as in answer C, or only the row with EMPLOYEE\_ID as in answer E, or the row with empty LAST\_NAME column.

Incorrect Answers

A: This answer is incorrect because a primary key cannot be NULL.

B: INSERT statement does not contain primary key value at all, so this answer needs to be eliminated as correct one.

D: This statement shows incorrect order of columns of row which needs to be inserted into the table.

OCP Introduction to Oracle 9i: SQL Exam Guide, Jason Couchman, p. 260-267  
Chapter 6: Manipulating Oracle Data

### QUESTION NO: 3

You need to give the MANAGER role the ability to select from, insert into, and modify existing rows in the STUDENT\_GRADES table. Anyone given this MANAGER role should be able to pass those privileges on to others.

Which statement accomplishes this?

- A.** GRANT select, insert, update  
ON student\_grades  
TO manager;
- B.** GRANT select, insert, update  
ON student\_grades  
TO ROLE manager;
- C.** GRANT select, insert, modify  
ON student\_grades  
TO manager  
WITH GRANT OPTION;
- D.** GRANT select, insert, update  
ON student\_grades  
TO manager

WITH GRANT OPTION;  
E. GRANT select, insert, update  
ON student\_grades  
TO ROLE manager  
WITH GRANT OPTION;  
F. F.GRANT select, insert, modify  
ON student\_grades  
TO ROLE manager  
WITH GRANT OPTION;

**Answer: D**

**Explanation:**

This answer provides correct syntax of GRANT command to give the MANAGER role all asked privileges. Clause WITH GRANT OPTION will allow this role to pass those privileges on to others.

**Incorrect Answers**

A: This statement would be correct if it included WITH GRANT OPTION clause to allow this role to pass those privileges on to others.

B: This statement uses incorrect clause TO ROLE.

C: There is no option with name MODIFY in the GRANT command.

E: This statement uses incorrect clause TO ROLE.

F: There is no option with name MODIFY in the GRANT command. And this statement also uses incorrect clause TO ROLE.

OCP Introduction to Oracle 9i: SQL Exam Guide, Jason Couchman, p. 356-365  
Chapter 8: User Access Control in Oracle

**QUESTION NO: 4**

Examine the data in the EMPLOYEES table:

LAST_NAME	DEPARTMENT_ID	SALARY
Getz	10	3000
Davis	20	1500
King	20	2200
Davis	30	5000
...		

Which three subqueries work? (Choose three)

- A.** SELECT \*  
FROM employees  
where salary > (SELECT MIN(salary)  
FROM employees  
GROUP BY department.id);
- B.** SELECT \*  
FROM employees  
WHERE salary = (SELECT AVG(salary)  
FROM employees  
GROUP BY department\_id);
- C.** SELECT distinct department\_id  
FROM employees  
Where salary >ANY (SELECT AVG(salary)  
FROM employees  
GROUP BY department\_id);
- D.** SELECT department\_id  
FROM employees  
WHERE SALARY > ALL (SELECT AVG(salary)  
FROM employees  
GROUP BY department\_id);
- E.** SELECT last\_name  
FROM employees  
Where salary > ANY (SELECT MAX(salary)  
FROM employees  
GROUP BY department\_id);
- F.** SELECT department\_id  
FROM employees  
WHERE salary > ALL (SELECT AVG(salary)  
FROM employees  
GROUP BY AVG(SALARY));

**Answer: C,D,E**

**Explanation:**

These answers show correct syntax, because they use ANY and ALL keywords for convert multi-row output of sub-query to one-row result.

**Incorrect Answers**

A: This SELECT statement is incorrect because of multi-row return of sub-query: it will return minimal salary for EACH department.

B: This SELECT statement is incorrect because of multi-row return of sub-query: it will return average salary for EACH department.

F: This SELECT statement is incorrect because GROUP BY clause cannot contain functions, like

AVG(), MIN(), MAX() and so on.

OCP Introduction to Oracle 9i: SQL Exam Guide, Jason Couchman, p. 145-156  
Chapter 4: Subqueries

### QUESTION NO: 5

The database administrator of your company created a public synonym called HR for the HUMAN\_RESOURCES table of the GENERAL schema, because many users frequently use this table.

As a user of the database, you created a table called HR in your schema. What happens when you execute this query?

```
SELECT *  
FROM HR;
```

- A. You obtain the results retrieved from the public synonym HR created by the database administrator.
- B. You obtain the results retrieved from the HR table that belongs to your schema.
- C. You get an error message because you cannot retrieve from a table that has the same name as a public synonym.
- D. You obtain the results retrieved from both the public synonym HR and the HR table that belongs to your schema, as a Cartesian product.
- E. You obtain the results retrieved from both the public synonym HR and the HR table that belongs to your schema, as a FULL JOIN.

**Answer: B**

**Explanation:**

By executing this query you will extract data from the HR table in your own schema, it will not work with HR synonym for the HUMAN\_RESOURCES table of the GENERAL schema.

Incorrect Answers

- A: The results will be retrieved from the table in your own schema, not from the GENERAL schema, using synonym HR.
- C: There is no error: data from the table in your own schema will be retrieved by this query.
- D: This query will not generate Cartesian product from both tables.
- E: This query will not retrieve data from both tables as a FULL JOIN.

OCP Introduction to Oracle 9i: SQL Exam Guide, Jason Couchman, p. 331-335  
Chapter 7: Creating Other Database Objects in Oracle

**QUESTION NO: 6**

Which two statements about views are true? (Choose two.)

- A. A view can be created as read only.
- B. A view can be created as a join on two or more tables.
- C. A view cannot have an ORDER BY clause in the SELECT statement.
- D. A view cannot be created with a GROUP BY clause in the SELECT statement.
- E. A view must have aliases defined for the column names in the SELECT statement.

**Answer: A,B**

**Explanation:**

A view can be created as read only object. However, it is possible to change data in the underlying table(s) with some restrictions. A view also can be created as a join on two or more tables. This type of view is called complex view. Complex views provide complicated data models where many base tables are drawn together into one virtual table.

**Incorrect Answers**

- C: Query operations containing ORDER BY clause are also permitted, so long as the ORDER BY clause appears outside the parentheses. The following is an example of what I mean: `CREATE VIEW my_view AS (SELECT * FROM emp) ORDER BY empno.`
- D: A view can be created with a GROUP BY clause in the SELECT statement.
- E: It is not required to have aliases defined for the column names in the SELECT statement.

OCP Introduction to Oracle 9i: SQL Exam Guide, Jason Couchman, p. 292-309  
Chapter 7: Creating Other Database Objects in Oracle

**QUESTION NO: 7**

Examine the description of the EMPLOYEES table:



EMP_ID	NUMBER(4)	NOT NULL
LAST_NAME	VARCHAR2(30)	NOT NULL
FIRST_NAME	VARCHAR2(30)	
DEPT_ID	NUMBER(2)	
JOB_CAT	VARCHAR2(30)	
SALARY	NUMBER(8,2)	

Which statement shows the maximum salary paid in each job category of each department?

- A. SELECT dept\_id, job\_cat, MAX(salary)  
FROM employees  
WHERE salary > MAX(salary);
- B. SELECT dept\_id, job\_cat, MAX(salary)  
FROM employees  
GROUP BY dept\_id, job\_cat;
- C. SELECT dept\_id, job\_cat, MAX(salary)  
FROM employees;
- D. SELECT dept\_id, job\_cat, MAX(salary)  
FROM employees  
GROUP BY dept\_id;
- E. SELECT dept\_id, job\_cat, MAX(salary)  
FROM employees  
GROUP BY dept\_id, job\_cat, salary;

**Answer: B**

**Explanation:**

This answer provides correct syntax and semantics to show the maximum salary paid in each job category of each department.

**Incorrect Answers**

- A: This query will not return any row because condition SALARY > MAX(SALARY) is FALSE.
- C: This query will return error because you cannot show maximum salary with DEPT\_ID and JOB\_CAT without grouping by these columns.
- D: The GROUP BY clause is missing JOB\_ID column.
- E: You don't need to group results of query by SALARY in the GROUP BY column.

OCP Introduction to Oracle 9i: SQL Exam Guide, Jason Couchman, p. 356-365

Chapter 8: User Access Control in Oracle

**QUESTION NO: 8**

Management has asked you to calculate the value  $12 * salary * commission\_pct$  for all the employees in the EMP table. The EMP table contains these columns:

LASTNAME	VARCHAR2(35) NOT NULL
SALARY	NUMBER(9,2) NOT NULL
COMMISION_PCT	NUMBER(4,2)

Which statement ensures that a value is displayed in the calculated columns for all employees?

- A. `SELECT last_name, 12*salary* commission_pct  
FROM emp;`
- B. `SELECT last_name, 12*salary* (commission_pct,0)  
FROM emp;`
- C. `SELECT last_name, 12*salary*(nvl(commission_pct,0))  
FROM emp;`
- D. `SELECT last_name, 12*salary*(decode(commission_pct,0))  
FROM emp;`

**Answer: C**

**Explanation:**

This SELECT statement provides correct usage of NVL function to calculate columns for all employees. Oracle give you possibility to substitute a value in place of NULL. The basic syntax for NVL() is NVL(column\_name, value\_if\_null). Notice that the column specified in NVL() contains an actual value. That value is what Oracle returns; when the column is NULL, the special string is returned. The value specified to be returned if the column value is NULL must be the same datatype as the column specified.

**Incorrect Answers**

- A: This SELECT statement will return NULL value for rows with NULL COMMISION\_PCT column.
- B: It is incorrect syntax in this query: NVL function needs to be used for correct result.
- D: The DECODE function is used as substitution of IF-THEN-ELSE PL/SQL construction in SQL queries. The SELECT statement provides incorrect syntax of it cannot have only two parameters.

OCP Introduction to Oracle 9i: SQL Exam Guide, Jason Couchman, p. 31-32  
Chapter 1: Overview of Oracle Databases