

Oracle 1z0-862

**Java Enterprise Edition 5 Web Services Developer
Certified Professional Exam**

Practice Test

Version: 14.20

QUESTION NO: 1

Which two statements are true about XML schemas and WSDL 1.1? (Choose two.)

- A. <http://schemas.xmlsoap.org/wsdl/> is the WSDL namespace for SOAP binding.
- B. xsi is used as a prefix to represent the schema namespace as defined by XSD
- C. XSD schemas are used as a formal definition of WSDL grammar.
- D. xsd is used as a prefix to represent the schema namespace as defined by XSD
- E. <http://schemas.xmlsoap.org/wsdl/http/> is the WSDL namespace for SOAP binding.

Answer: C,D

QUESTION NO: 2

A company's new investment management Java application and a legacy stock trader application need to communicate, but they use different JMS implementations. A developer decides to implement a JMS bridge to solve the problem. Which two advantages does this pattern provide? (Choose two.)

- A. It converts the interface of a class into another interface that clients expect.
- B. It decouples an abstraction from its implementation so that the two can vary independently.
- C. It dynamically attaches additional responsibilities to an object.
- D. It optimizes network traffic.
- E. It is vendor independent.

Answer: B,E

QUESTION NO: 3

Which situation requires the client to use the Dispatch interface to access the Web service?

- A. The client and the server are on different platforms.
- B. The client has access to the portable artifacts, but not to the WSDL.
- C. The client has access to the WSDL, but not to the portable artifacts.
- D. The client will access a REST-based service.

Answer: D

QUESTION NO: 4

What are two features of a WSDL 1.1 document? (Choose two.)

- A. Service defines a collection of related endpoints.
- B. Service describes the message's payload using XML.
- C. Service assigns an Internet address to a specific binding.
- D. Porttype declares complex data types and elements used elsewhere.
- E. Porttype elements are used to group a set of abstract operations.
- F. Porttype defines a concrete protocol and data format specification.

Answer: A,E

QUESTION NO: 5

Which three can an EJB-based endpoint use? (Choose three.)

- A. HTTP sessions
- B. Java EE 5 declarative security
- C. Java EE 5 programmatic security
- D. client-demarcated transactions
- E. container-managed transactions

Answer: B,C,E

QUESTION NO: 6

What are two communication modes supported by JAX-WS? (Choose two.)

- A. Synchronous RPC
- B. Dynamic Service Binding
- C. Dynamic Proxy
- D. Endpoint Invocation
- E. Dispatch

Answer: C,E

QUESTION NO: 7

A company is refactoring an existing website to use Web services clients. The application retrieves lists of parts and displays them to the users in a browser window. Previously, the data was stored as files on the web server and, in order to access the files, the user

would simply click on a hyperlink. Now the data must be dynamically generated via a service that another developer has created. They want the easiest way to refactor their website to use Web services. Which three technologies should they use? (Choose three.)

- A. SOAP
- B. REST
- C. Javascript
- D. XML
- E. JSON
- F. Java

Answer: B,C,E

QUESTION NO: 8

A JAXR client has established connection with a UDDI registry and needs to get a service binding from the registry. What is required to accomplish this task?

- A. find the appropriate concept and then find the service binding associated with that concept
- B. find the appropriate authentication token and then find the service binding associated with that authentication token
- C. find the appropriate organization, get the tModel associated with that organization, and then find the service binding associated with the tModel
- D. find the appropriate organization, find the services associated with that organization, and then find the service binding associated with the service

Answer: D

QUESTION NO: 9

What are three benefits of using SSL to connect to a Web service without mutual authentication? (Choose three.)

- A. The server is assured of the client's identity if the client issues the certificate.
- B. The client is assured of the server's identity.
- C. Message integrity is preserved between the client and the server.
- D. The communication between the client and the server is still logged.
- E. The communication between the client and the server is encrypted.
- F. Using SSL over HTTP incurs less overhead than HTTPS.

Answer: B,C,E

Explanation:

QUESTION NO: 10

A developer is creating a servlet-based endpoint for a new payroll application. What are three requirements for the service? (Choose three.)

- A. It needs to be packaged as a WAR file.
- B. It needs to be packaged as a JAR file.
- C. It requires a META-INF folder.
- D. It requires a WEB-INF folder.
- E. webservices.xml is required.
- F. web.xml is required.

Answer: A,D,F

QUESTION NO: 11

A developer is creating an XML schema that is Basic Profile compliant, and has elements that require long integer values.

Given the code:

```
<Schema targetNamespace="http://sun.cert/types"
xmlns:ns0="http://www.w3.org/2001/XMLSchema"
xmlns="http://www.w3.org/2001/XMLSchema" xmlns:xsd="http://sun.cert/xsdTypes"
xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance">
<complexType name="Foo">
<sequence>
<!-- insert code here -->
</sequence>
</complexType>
</schema>
```

Assuming that no other namespace declarations exist, which two elements use the long

type that is defined in the `http://www.w3.org/2001/XMLSchema` namespace? (Choose two.)

- A. `<element name="length" type="long"/>`
- B. `<element name="length type="xsi:long"/>`
- C. `<element name="length" type="xsd:long"/>`
- D. `<element name="length" type="ns0:long"/>`
- E. `<element name="length" type="integer"/>`
- F. `<element name="length" type="xsd:integer"/>`

Answer: A,D

QUESTION NO: 12

A developer needs to define an array of long integers in their Basic Profile compliant Web service and is given the following code fragment for analysis:

```
<Schema targetNamespace="http://sun.cert/types"
xmlns:xsd="http://www.w3.org/2001/XMLSchema"
xmlns:soapenc="http://schemas.xmlsoap.org/soap/encoding/"
xmlns:wSDL="http://schemas/xmlsoap.org/wSDL">
<!-- insert code here -->
</schema>
```

Assume all XML fragments are well-formed. According to the WS-I Basic Profile 1.1, which type definition can be used to define an array of longs?

- A. `<xsd:complexType name="longArray">`
`<xsd:array>`
`<xsd:element name="item" type="xsd:long"/>`
`</xsd:array>`
`</xsd:complexType>`
- B. `<xsd:complexType name="longArray">`
`<xsd:sequence>`
`<element name="item" type="xsd:long"/>`
`</xsd:sequence>`
`</xsd:complexType>`
- C. `<xsd:complexType name="longArray">`
`<xsd:array>`
`<xsd:element name="item" type="xsd:long" minOccurs="0" maxOccurs="unbounded"/>`
`</xsd:array>`

```
</xsd:complexType>
D. <xsd:complexType name="longArray">
  <xsd:sequence>
  <xsd:element name="item" minOccurs="0" maxOccurs="5" type="xsd:long"/>
  </xsd:sequence>
</xsd:complexType>
E. <xsd:complexType name="longArray">
  <xsd:sequence>
  <xsd:element name="item" minOccurs="0" maxOccurs="5" type="xsd:integer"/>
  </xsd:sequence>
</xsd:complexType>
```

Answer: D

QUESTION NO: 13

A developer is creating an XML schema using the xsd:all operator. Given the code:

```
<types>
<schema targetNamespace="http://sun.cert/types" xmlns:tns="http://sun.cert/types"
xmlns:xsd="http://www.w3.org/2001/XMLSchema">
  <xsd:complexType name="Person">
  <xsd:all>
  <!-- insert code here -->
  </xsd:all>
</xsd:complexType>
</schema>
</types>
```

Which two element definitions, when inserted into the given schema fragment, result in a correct schema type definition? (Choose two.)

- A. <xsd:element name="first" type="xsd:string"/>
- B. <xsd:element name="items" type="xsd:long" maxOccurs="5"/>
- C. <xsd:element name="last" type="xsd:string" minOccurs="1" maxOccurs="1"/>
- D. <xsd:element name="first" type="xsd:string" minOccurs="0" maxOccurs="5"/>
- E. <xsd:element name="last" type="xsd:string" minOccurs="1" maxOccurs="5"/>
- F. <xsd:element name="ssn" type="xsd:string" minOccurs="1" maxOccurs="unlimited"/>

Answer: A,C

QUESTION NO: 14

A developer must create a new stock monitoring application using SOAP.

Given the code:

```
<s:Envelope xmlns:s="http://schemas.xmlsoap.org/soap/envelope/"
xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xmlns:xsd="http://www.w3.org/2001/XMLSchema" xmlns:ns1="http://sun.cert/">
<s:Header>
<ns1:transaction>
<user>root</user>
<transid>9b3e64e326537b4e8c0ff19e953f9673</transid>
</ns1:transaction>
</s:Header>
<s:Body>
<m:StockQuote xmlns:m="http://sun.cert/bar/">
<Quote>
<ns1:symbol>SUNW</ns1:symbol>
<ns1:companyname name="Sun"/>
</Quote>
</s:Body>
</s:Envelope>
```

Which statement is true about this SOAP message?

- A.** It is NOT well-formed.
- B.** It contains a mandatory header block.
- C.** It is WS-I Basic Profile 1.1 compliant.
- D.** It does NOT contain the correct namespace declarations.
- E.** The transid should be blowfish encrypted.
- F.** `http://sun.cert/bar/` is not a valid stock quote service.

Answer: A

QUESTION NO: 15

A team of developers is describing a set of endpoints in their new SOA application.

Given the WSDL extract:

```
<service name="InventoryServices">
  <port name="PurchaseOrder" binding="tns:POBinding">
    <soap:address location="http://192.168.0.2:8080/inventory"/>
  </port>
  <port name="Invoice" binding="tns:InvoiceBinding">
    <soap:address location="http://192.168.0.2:8080/inventory"/>
  </port>
</service>
```

Which statement is true about this WSDL extract?

- A.** The extract is WS-I Basic Profile 1.1 compliant because both port element names are different.
- B.** The extract is NOT WS-I Basic Profile 1.1 compliant because both port elements point to the same location.
- C.** The extract is WS-I Basic Profile 1.1 compliant because both port elements point to different binding elements.
- D.** The extract is NOT WS-I Basic Profile 1.1 compliant because it contains two port elements in the same service.
- E.** The extract is WS-I Basic Profile 1.1 conformant because both port element names are different.
- F.** The extract is WS-I Basic Profile 1.1 conformant because the port, binding, and service element combinations are unique.

Answer: B

QUESTION NO: 16

Which two statements are true about XML schemas that conform to WS-I Basic Profile

1.1? (Choose two.)

- A. A description may use any construct from XML Schema.
- B. A description may use any construct of XML Schema, except for arrays.
- C. A description must use XML Schema recommendations as the basis of userdefined datatypes and structures.
- D. A description may use any construct of XML Schema, except for defining userdefined datatypes and structures.
- E. RESTful XML schemas may also draw from the XML-Rest Schema.

Answer: A,C

QUESTION NO: 17

A developer is defining a SOAP binding in the WSDL for their new service. Which XML fragment is WSDL 1.1 compliant?

- A. `<soap:binding transport=Http://www.w3.org/2001/XMLSchema?style="document"/>`
- B. `<soap:binding transport=Http://schemas.xmlsoap.org/wsdl/soap/?style="document"/>`
- C. `<soap:binding transport=Http://schemas.xmlsoap.org/soap/http?style="document"/>`
- D. `<soap:binding transport=Http://schemas.xmlsoap.org/soap?style="rpc"/>`

Answer: C

QUESTION NO: 18

Which fragment is Basic Profile 1.1 compliant?

- A. `<port name="testWS"> <operation name="runit">
<input message="tns:runit"/>
<output message="tns:runitResponse"/>
</operation>
</port>
<binding name="testWSPortBinding" type="tns:testWS">
...
<operation name="runit">
<soap:operation soapAction="tns:runit"/>
<input>
<soap:body use="literal"/>
</input>
<output>
<soap:body use="literal"/>
</output>
</operation>
</binding>`