



Implementing Cisco Service Provider Mobile Unlicensed Small Cell Solutions

Version: 6.0

[Total Questions: 51]

https://certkill.com

CERTKILL

Question No:1

A primary goal of the Cisco Service Provider Wi-Fi solution is to provide an exceptional user experience. From the point of view of the service provider, which two factors affect the user experience? (Choose two.)

- A. how the user gains access to the network
- B. how services and policies are applied to the user
- C. how the user traffic is routed to the Internet
- D. the path that the user traffic has to follow to reach the Internet
- E. how the service providers monetize their network

Answer: A,B

Question No:2

Cisco intelligent access points provide four features that can be used to enhance the user experience.

Which three features are available on Cisco intelligent access points? (Choose three.)

- A. Cisco CleanAir
- B. Cisco DataSecure
- C. Cisco ClientLink
- **D.** Cisco BandSelect
- E. Cisco VoiceProtect
- F. Cisco Streaming Video

Answer: A,C,D

Question No:3

Wi-Fi Passpoint is a Wi-Fi Alliance certification program and it is often used synonymously with the name of the technology that the Passpoint program certifies devices as being compliant with.

Which technology does Passpoint certification assure compliance with?

A. Next-Generation Hotspot

B. Wi-Fi Protected AccessC. Hotspot 2.0D. Wi-Fi Protected Access 2

Answer: C

Question No:4

In what way does MAC-TAL authentication improve the user experience?

A. The services and policies of each user are applied automatically as part of the authentication process, based on the user's MAC address.

B. If the user is disconnected during a session, they are re-authenticated automatically based on their MAC address.

C. When the user first connects to the network, they are redirected to a personalized web portal based on their MAC address.

D. Layer 2 security mechanisms can be applied separately to each user, based on their MAC address.

Answer: B

Question No:5

Which benefit is provided by link aggregation in the Cisco 8500 Series Controller?

- A. higher capacity and reliability by using eight 1 GbE ports
- B. higher capacity and reliability by using two 10 GbE ports
- C. higher reliability by using two 10 GbE ports
- D. high reliability by using eight 1 GbE ports

Answer: C

Question No : 6

Which option does EAP-SIM authentication require?

A. the latest Cisco WLC software (Previous software versions only supported PEAP MS-