

Cisco 642-654

**642-654 Wide Area Application Services for System
Engineers (WAASSE)**

Practice Test

Version 2.7

QUESTION NO: 1

With Cisco WAAS advanced compression DRE, which three functions are performed during the DRE process? (Choose three.)

- A. Pattern matching
- B. Synchronization
- C. LZ compression
- D. Fingerprint and chunk identification

Answer: A,B,D

QUESTION NO: 2

Do you know how often the Cisco WAAS automatic discovery takes place?

- A. Once per user
- B. Every hour
- C. On a Connection-by-Connection basis
- D. Once per office

Answer: C

QUESTION NO: 3

What is the status of Cisco WAAS optimization after completing the quick start process on all devices and installing the enterprise license? (Choose two.)

- A. Cisco WAAS is ready for the Central Manager to be configured to optimized traffic
- B. Cisco WAAS is ready for bandwidth settings to be defined for communication
- C. Cisco WAAS application optimizers are enabled
- D. Default optimizations are applied traffic passing through the Cisco WAE devices

Answer: C,D

QUESTION NO: 4

Which two statements describe what is required for read-only disconnected mode to be automatically activated during a prolonged WAAS disconnect? (Choose two.)

- A. The WAE must be configured for Windows Authentication
- B. The Windows server must be configured for operating in disconnected mode

- C. The WAE must be able to access a Window Domain Controller
- D. The WAE must be joined to the same workgroup as the Windows Server

Answer: A,C

QUESTION NO: 5

Which three are high-availability Cisco WAE solutions for a branch office? (Choose three.)

- A. PBR
- B. WCCP
- C. Multiple Cisco WAE devices with inline cards
- D. Firewall load-balancing Cisco WAE devices

Answer: A,B,C

QUESTION NO: 6

The Cisco WAAS design of your customer calls for the Central Manager to be deployed on the Core WAE, which is a WAE-612 with 2 GB of RAM. The customer initially configured the WAE as an application accelerator and then issued the device mode central-manager command to enable Central Manager Service. Now the customer complains that the WAE is no longer accelerating traffic why?

- A. The Central Manager and application accelerator cannot be deployed on the same WAE
- B. The device mode central-manager command must be issued before the device mode application-accelerator command
- C. At least 4 GB of RAM must be installed for the WAE to serve as both Central Manager and application accelerator
- D. Central Manager is consuming too much CPU time on the WAE. The Central Managerservice should be implemented on a less-utilized edge WAE

Answer: A

QUESTION NO: 7

Which two benefits can we get by using Cisco WAAS with Cisco security devices such as Cisco PIX, Cisco ASA and Cisco IOS Firewalls? (Choose two.)

- A. The security devices will speed Cisco WAAS transport
- B. The security devices support the TCP sequence number jump that Cisco WAAS uses

- C. Cisco WASS requires Cisco Security devices to be installed
- D. The security devices can be configured to support Cisco WAAS automatic discovery

Answer: B,D

QUESTION NO: 8

In Order to ensure Cisco WAAS Mobile transport and management, which three protocols and ports need to be allowed through corporate firewalls? (Choose three.)

- A. TCP 80
- B. TCP 8080
- C. UDP 8080
- D. UDP 1182

Answer: A,B,D

QUESTION NO: 9

SACK improves performance for which type of traffic?

- A. Short-lived TCP connections
- B. Traffic on high-BDP networks
- C. Traffic on lossy networks
- D. Traffic on low-BDP networks

Answer: C

QUESTION NO: 10

Which parameter should be taken into consideration while selecting a Cisco WAE model for a Cisco WAAS deployment?

- A. Bandwidth of the largest WAN Link
- B. Total WAN throughput
- C. Concurrent TCP sessions to be optimized
- D. Bandwidth of the smallest WAN link

Answer: C

QUESTION NO: 11

Which three match conditions are valid for traffic classifiers in a WAAS Application Traffic Policy?
(Choose three.)

- A. Routing
- B. TCP Port
- C. Subnet
- D. IP Routing

Answer: B,C,D

QUESTION NO: 12

Your customer is using PBR as the interception method on its routers. Which mechanism would you recommend to ensure WAE availability and failover if a WAE fails?

- A. Enable IP SLAs to track WAE appliances
- B. Enable NetFlow to track WAE appliances
- C. Nothing, PBR does not support the tracking of WAE appliances
- D. Nothing, PBR automatically tracks WAE appliances

Answer: A

QUESTION NO: 13

One of your customers would like to use Active Directory to manage authentication for WAE administrative users. How to configure authentication in the Cisco WAAS Central Manager?

- A. Configure RADIUS services on the Active Directory server and set RADIUS as the primary login method
- B. Configure Active Directory as the primary login method
- C. Configure LDAP services on the Active Directory server and set LDAP as the primary login method
- D. Configure TACACS+ services on the Active Directory server and set TACACS+ as the primary login method

Answer: B

QUESTION NO: 14