

Aruba

Exam ACMP_6.3

Aruba Certified Mobility Professional 6.3

Version: 6.0

[Total Questions: 165]

Aruba ACMP_6.3 : Practice Test

Question No: 1

Which of the following Aruba controllers is able to provide IEEE 802.3af? (Choose two)

- **A.** 3200
- **B.** 620
- **C.** 650
- **D.** 6000 with M3
- **E.** 7000

Answer: B,C

Question No: 2

What is the maximum number of remote APs supported by a 3600 controller?

- **A.** 512
- **B.** 1024
- **C.** 128
- **D.** 256
- **E.** 2048

Answer: A

Question No: 3

Which dual radio access point models support concurrent operations in the 2.4Ghz band as well as the 5Ghz band? (Choose three)

- **A.** AP-92
- **B.** AP-93
- **C.** AP-105
- **D.** AP-224
- **E.** AP-135

Answer: C,D,E

Question No: 4

Aruba ACMP_6.3: Practice Test

Which of the following APs do NOT support dual radio operations?(Choose two)

- **A.** AP 93
- **B.** AP 105
- C. RAP 3WN
- **D.** AP 224
- **E.** AP 135

Answer: A,C

Question No:5

Centralized licensing is not in use on an Aruba based network which has a Master and three local controllers. No APs terminate on the Master controller. Roles and Firewall policies need to be created and applied, hence PEF-NG license is required

On which controller should the license be installed?

- **A.** Only the master controller since role and firewall policies are created here.
- **B.** Only the local controllers since firewall policies are applied here
- C. The master and all three local controllers
- **D.** This isn't the correct license for this purpose, use PEF-VPN license
- E. This is not needed because PEF-NG is part of base OS

Answer: C

Question No: 6

What information do you need to generate a feature license key for an Aruba controller?

- A. The controller's MAC address and the feature description.
- B. Controller's MAC address and the certificate number
- C. Controller's Serial Number and the feature description
- **D.** Controller's Serial Number and the certificate number
- E. Controller's MAC address and Serial Number

Answer: D



Question No:7

What are the PEF-NG license limits based on?

- A. Number of APs
- B. One license per controller
- C. Number of users
- D. Number of local controllers
- E. Master Controller total user count

Answer: A

Question No:8

Which of the following licenses are consumed by Mesh APs advertising an SSIDs?

- A. AP license
- B. Mesh license
- C. PEF-V license
- D. No license is required
- E. RAP License

Answer: A

Question No:9

The permanent licenses on the controller will be deleted with the use of which command?

- A. Delete license
- B. Write erase
- C. Licenses cannot be deleted once activated
- **D.** Write erase all
- E. Reboot delete all

Answer: D

Question No: 10

A network administrator wants to terminate VPN sessions on a local controller in the DMZ. Which statement is true about the PEF-VPN license?

- A. It is only applied to the master controller
- **B.** It is only applied to the DMZ controller.
- C. It is based on the number of APs
- **D.** One license is needed on the master and the DMZ local
- E. It is distributed by the license server as needed

Answer: D

Question No: 11

What is the best practice regarding licensing for a backup master to support Master Redundancy in a network without centralized licensing?

- A. Backup master only requires the AP license
- **B.** Supported limits and installed licenses should be the same on primary master and backup Master
- **C.** Licenses are pushed from the primary to the backup Master along with the configuration
- **D.** The Backup Master does not require licenses to support master redundancy
- **E.** On the backup only one license of each typeis needed.

Answer: B

Question No: 12

Which of the following licenses can be included in the licensing pool for centralized licensing? (Choose three)

- A. Factory default licenses
- B. PEFNG license
- C. Evaluation licenses
- D. RFProtect license
- E. PEFV license

Answer: B,C,D



Question No: 13

By default Centralized licensing messages between master controllers are sent

_____•

- A. In the clear unencrypted
- B. Using CPSec
- C. Using IPSec site to site VPN tunnels
- **D.** Encrypted using GRE
- E. PAPI

Answer: A

Question No: 14

Which of the following will occur if a master license server fails with no standby server present? (Choose two)

- A. Local controllers licenses will continue to be valid for 30 days
- B. Local controllers will immediately remove all installed licenses
- C. No licenses will be sent to any new controllers that come online
- **D.** All licenses go back into the pool for redistribution
- E. A Local Controller elects itself master license server

Answer: A,C

Question No: 15

Which may be applied directly to an VLAN interface? (Choose three)

- A. Access List (ACL)
- **B.** Firewall Policy
- C. Roles
- D. AAA profiles
- E. RF Plan Map

Answer: A,B,D

Question No: 16

When creating a firewall rule on an Aruba controller, which parameter is optional?

- A. Destination
- B. Service
- C. Source
- D. Log
- E. Action

Answer: D

Question No: 17

An administrator creates a WLAN with an unmodified default AAA profile. What is the default role the user is placed in?

- A. default-logon
- **B.** logon
- C. guest-logon
- **D.** default-ap
- E. AP-Role

Answer: B

Question No: 18

What is the first role a user is given when a user associates to an open WLAN?

- A. The guest post authentication role
- **B.** The initial role in the captive portal profile
- **C.** The role in the server group profile
- **D.** The initial role in the AAA profile
- **E.** The initial role in the 802.1x profile



Answer: D

Question No: 19

Which of the following could be used to set a user's post-authentication role or VLAN association? (Choose two)

- A. AAA default role for authentication method
- B. Server Derivation Rule
- C. Vendor Specific Attributes
- D. AP Derivation Rule
- E. The Global AAA profile

Answer: B,C

Question No: 20

Which describe "roles" as used on Aruba Mobility Controllers? (Choose two)

- **A.** Roles are assigned to users.
- **B.** Roles are applied to interfaces.
- **C.** Policies are built from roles.
- **D.** A user can belong to only one role at a time.
- E. Roles are a set of authentication rules

Answer: A,D

Question No: 21

Which netdestination aliases are built into the controller? (Choose three)

- A. logon
- **B.** any
- C. user
- **D.** guest
- E. localip



Answer: B,C,E

Question No: 22

What are aliases used for?

- A. Improve controller performance
- **B.** Simplify the configuration process
- C. Tie IP addresses to ports
- D. Assign rules to policies
- E. Assign policies to roles

Answer: B

Question No: 23

Which of the following firewall rules allows a user to initiate an ICMP session to other devices? (Choose two)

- A. localip any svc-icmp permit
- B. user any svc-icmp permit
- C. user user svc-icmp permit
- D. any any svc-icmp permit
- E. mswitch any svc-icmp permit

Answer: B,D

Question No: 24

The Aruba Policy Enforcement Firewall (PEF-NG) module supports destination network address translation (dst-nat).

Which is the default use of this statement in an Aruba controller configuration?

- **A.** Source the IP addresses of users to specific IP address
- B. Redirect HTTP sessions to Captive Portal

Aruba ACMP_6.3 : Practice Test

- C. Redirect Access Points to another Aruba controller
- **D.** Provide a telnet connection to the controller
- E. Redirect a SSH session to terminate on the controller

Answer: B

Question No: 25

The Aruba Policy Enforcement Firewall (PEF) module supports source network address translation (src-nat).

Which is a use of this statement in an Aruba configuration?

- A. Provide a single source IP address for users in a role
- B. Redirect Captive Portal HTTP sessions
- C. Redirect Access Points to another Aruba controller
- D. Provide IP addresses to clients
- E. Redirects clients to Aruba Firewall

Answer: A

Question No: 26

The network administrator wishes to terminate the VPN encryption on the Aruba controller.

When writing a firewall rule to accomplish the task of automatically moving the VPN traffic for the wireless clients from a third party VPN concentrator to an Aruba controller, which action needs to be configured in the rule?

- A. redirect to IPSec Group
- B. source NAT
- C. destination NAT
- **D.** redirect to tunnel
- E. redirect to GRE

Answer: C