

IBM

Exam C9510-819

Rational Application Developer V8 Associate

Version: 6.0

[Total Questions: 60]

Question No : 1

Each server profile created with Rational Application Developer has its own what?

- A. libraries
- B. runtime scripts
- C. administrative console
- D. Java runtime environment

Answer: C

Question No : 2

Which projects can be deployed to a WebSphere Application Server test environment in Rational Application Developer?

- A. Dynamic Web
- B. Enterprise Application
- C. Enterprise Java Bean
- D. Application Client

Answer: B

Question No : 3

A developer needs to debug an application on Rational Application Developer. How can the developer add breakpoints in the code?

- A. enable System.out.println on the code
- B. select Window -> Preferences -> Debug -> Breakpoints -> Enable on the application code
- C. click on the gray area of the left frame on the line of code for which breakpoint is required
- D. enable Tracing on the server with breakpoint

Answer: C

Question No : 4

Which term refers to the set of files that defines the runtime environment of a WebSphere Application Server?

- A. script set
- B. profile
- C. installation
- D. node

Answer: B

Question No : 5

There is a simple named query defined in the following way:

```
@NamedQuery(name=etCustomer? query=elect c from Customer c?@NamedQuery(name=?etCustomer? query=?elect c from Customer c? Which Entity Manager (em) method must be used to access this defined named query?
```

- A. Query q = em.createNamedQuery(etCustomer?;Query q = em.createNamedQuery(?etCustomer?;
- B. Query q = em.createQueryByName(etCustomer?;Query q = em.createQueryByName(?etCustomer?;
- C. Query q = em.findNamedQuery(etCustomer?;Query q = em.findNamedQuery(?etCustomer?;
- D. Query q = em.getNamedQuery(etCustomer?;Query q = em.getNamedQuery(?etCustomer?;

Answer: A

Question No : 6

A developer needs to disable breakpoint on an application on Rational Application Developer. How can the developer remove breakpoint from the code?

- A. right-click on breakpoint and select Disable Breakpoint
- B. disable System.out.println on the code for having a breakpoint
- C. select Window -> Preferences -> Debug -> Breakpoints -> Disable on the application code
- D. disable Tracing on the server with breakpoint

Answer: A

Question No : 7

To test defined JPA entities, the Entity Manager must be created. Which expression creates the Entity Manager when the project name is the same as the persistence-unit name "RAD8JPA"?

- A. EntityManager em = Persistence.createEntityManagerFactory.createEntityManager();
- B. EntityManager em = Persistence("RAD8JPA").createEntityManagerFactory().createEntityManager();
- C. EntityManager em = Persistence.createEntityManagerFactory("RAD8JPA").createEntityManager();
- D. EntityManager em = Persistence.createEntityManagerFactory().createEntityManager("RAD8JPA");

Answer: C

Question No : 8

A developer has modified the Java perspective by adding and relocating views in the Rational Application Developer workbench. What should the developer select in order to keep the customizations?

- A. Window > Save Workbench As
- B. Window > Save Perspective As
- C. File > Save Views As
- D. File > Save Preferences As

Answer: B

Question No : 9

Which web services client type can you create in RAD 8?

- A. Java Proxy
- B. Service Proxy