

Hitachi

Exam HH0-330

HDS Storage Manager-Business Continuity Enterprise

Version: 6.0

[Total Questions: 58]

Question No : 1

Where do you find the "horcmstart.sh" command in a default CCI installation in a UNIX system?

- A. /usr/bin/
- B. /usr/sbin
- C. /HORCM/
- D. /HORCM/usr/bin/

Answer: D

Question No : 2

A pairresync operation is performed on a ShadowImage pair in a PSUE state.

What is the result of the pairresync operation?

- A. The pairresync completes immediately.
- B. All data on the P-Vol are copied to the S-Vol.
- C. The pairresync returns an error because of the PSUE state.
- D. The bitmaps are used and only changed tracks are copied from the P-Vol to the S-Vol

Answer: B

Question No : 3

Which two statements describe the Command Device? (Choose two.)

- A. The Command Device is user selected.
- B. The Command Device is system selected.
- C. The Command Device is a dedicated logical volume on the system which controls the CCI software on the UNIX/PC host.
- D. The Command Device is a dedicated logical volume on the system which functions as the interface to the CCI software on the UNIX/PC host.

Answer: A,D

Question No : 4

Which two statements describe the Command Device on UNIX systems? (Choose two.)

- A. The volume designated as the Command Device is a raw device.
- B. The volume designated as the Command Device is a block device.
- C. The Command Device accepts TrueCopy software and ShadowImage software read and write commands that are executed by the CCI software.
- D. The Command Device accepts TrueCopy software and ShadowImage software read and write commands that are executed by the storage system.

Answer: A,D

Question No : 5

Which two statements describe the Command Device? (Choose two.)

- A. The Command Device is for CCI communications and can be fully utilized by other applications.
- B. The Command Device is dedicated to CCI communications and should not be used by any other applications.
- C. The Command Device accepts TrueCopy and ShadowImage software read and write commands that are executed by the storage system.
- D. The Command Device accepts TrueCopy and ShadowImage software read and write commands that are executed by the CCI software.

Answer: B,C

Question No : 6

You are looking at the possibility of configuring the Raid Manager software.

Which three devices could be used as a CCI Command Device? (Choose three.)

- A. 3390-3 LUN
- B. LUSE LUN
- C. OPEN-V LUN
- D. OPEN-3 LUN
- E. Virtual LVI/LUN

Answer: C,D,E

Question No : 7

The CCI instance has failed to start.

What is the most likely cause?

- A. The Command Device is labeled.
- B. The environment variable HORCC_MRCF is set.
- C. The environment variable HORCMINST is not set.
- D. The IP address is not referenced in the HORCM file.

Answer: D

Question No : 8

The CCI instance needs to communicate with the storage system using the Command Device.

Which command should be executed to discover the name of the Command Device on a Windows server?

- A. `raidscan -x findcmddev hdisk 0,20`
- B. `raidscan -find commanddev hdisk 0,20`
- C. `raidscan -x find commanddev hdisk 0,20`
- D. `raidscan -find commanddevice hdisk 0,20`

Answer: A

Question No : 9

On a Windows system, how do you make sure that the environment parameter is set correctly to use CCI for ShadowImage operations instead of TrueCopy operations?

- A. Verify that HORCC_MRCF is set to 1.
- B. Verify that HORCM_MRCF is not set.