

# Juniper JN0-532

## **FWV, Specialist (JNCIS -FWV)**

**Version: 6.0**

**QUESTION NO: 1**

You have entered the following BGP configuration:

- Setvrouter trust-vr bgp 65530
- Setvrouter trust-vr bgp enable
- Setvrouter trust-vr protocol bgp neighbor 1.1.1.250 remote-as 65500
- Setvrouter trust-vr protocol bgp neighbor 1.2.3.250 remote-as 65280

BGP is not working. What two elements are missing from your configuration? (Choose two.)

- A. You have not enabled the BGP peers.
- B. You have not enabled EBGP multihop.
- C. You have not placed the peers in a BGP peer group.
- D. You have not enabled BGP on the interfaces connecting to the peers.

**Answer: A,D**

**Explanation:**

**QUESTION NO: 2**

Which of the following protocols is required in order to deploy AutoConnect-VPNs?

- A. PKI
- B. OSPF
- C. NSRP
- D. NHRP

**Answer: D**

**Explanation:**

**QUESTION NO: 3**

What are three components that make up a redundant VPN configuration? (Choose three.)

- A. master
- B. targets
- C. monitor
- D. backups
- E. VPN groups

**Answer: B,C,E**

**Explanation:**

**QUESTION NO: 4**

Which ScreenOS CLI command(s) allow(s) for redistribution of type 1-3 LSAs?

- A. set ospf export route external
- B. set match route-type internal-ospf
- C. set redistribute ospf lsa 1  
set redistribute ospf lsa 2  
set redistribute ospf lsa 3
- D. set protocol ospf lsa 1 redistribute  
set protocol ospf lsa 2 redistribute  
set protocol ospf lsa 3 redistribute

**Answer: B**

**Explanation:**

**QUESTION NO: 5**

What must be configured differently for a route-based VPN and a policy-based VPN?

- A. proxy-id
- B. proposals
- C. remote gateway type
- D. binding the tunnel interface

**Answer: D**

**Explanation:**

**QUESTION NO: 6**

Which ScreenOS CLI command is necessary for configuring IGMP on interface ethernet0/1?

- A. set igmp interface ethernet0/1
- B. set multicast interface ethernet0/1
- C. set interface ethernet0/1 igmp router

D. set igmp interface ethernet0/1 enable

**Answer: C**

**Explanation:**

### QUESTION NO: 7

During main mode negotiations a failure has occurred while using IKE certificates.

Which message pair would you review to troubleshoot this failure?

- A. messages 1 & 2
- B. messages 2 & 3
- C. messages 3 & 4
- D. messages 5 & 6

**Answer: D**

**Explanation:**

### QUESTION NO: 8

You enable run time object (RTO) sync on the NSRP cluster.

Which command will provide RTO message sync counters?

- A. get nsrp rto
- B. get count stat
- C. get rto counter
- D. get nsrp counter

**Answer: D**

**Explanation:**

### QUESTION NO: 9

When configuring ScreenOS, which three are OSPF area types? (Choose three.)

- A. stub
- B. virtual
- C. normal
- D. ordinary
- E. not-so-stubby

**Answer: A,C,E**

**Explanation:**

#### QUESTION NO: 10

Which statement about integrated Web filtering is true?

- A. You must configure a category profile.
- B. You must add categories to the black list and white list.
- C. User-defined categories are searched after pre-defined categories.
- D. The local cache contains the black list, white list, and all URLs in the user-defined categories.

**Answer: D**

**Explanation:**

#### QUESTION NO: 11

Using VSYS profiles, which three can you limit on a per-VSYS basis? (Choose three.)

- A. zones
- B. sessions
- C. subinterfaces
- D. CPU allocation
- E. memory allocation

**Answer: A,B,D**

**Explanation:**

#### QUESTION NO: 12

What must be enabled to protect Phase 2 key exchanges?

- A. Phase 1 PFS
- B. Phase 2 SHA
- C. Phase 2 3-DES
- D. Phase 2 DH key exchange

**Answer: D**

**Explanation:**

#### **QUESTION NO: 13**

When using NSRP, which command will ensure uninterrupted communications for VPNs using certificates for authentication?

- A. set hostname
- B. set NSRP clustername
- C. set NSRP cluster name
- D. set NSRP cluster hostname

**Answer: C**

**Explanation:**

#### **QUESTION NO: 14**

Which three interface types are supported in virtual systems? (Choose three.)

- A. subinterfaces
- B. VPN interfaces
- C. shared Interfaces
- D. limited Interfaces
- E. dedicated Interfaces

**Answer: A,C,E**

**Explanation:**

#### **QUESTION NO: 15**

When enabling OSPF over a hub and spoke VPN, what must you configure on the hub device tunnel interface to allow spokes to receive routing updates?

- A. Point to multipoint
- B. Disable split-horizon
- C. Enable demand circuit
- D. Enable passive interface

**Answer: A**

**Explanation:**

#### QUESTION NO: 16

You suspect you are having encryption problems with an IKE VPN.

Which two commands would help you determine if it is an encryption issue? (Choose two.)

- A. get counter screen <zone>
- B. get counter flow interface <name>
- C. get counter policy <policy number>
- D. get counter statistics interface <name>

**Answer: B,D**

**Explanation:**

#### QUESTION NO: 17

What should you configure to ensure an HA cable failure does not result in both devices attempting to become master?

- A. failover count
- B. secondary path
- C. monitor threshold
- D. heartbeat threshold

**Answer: B**

**Explanation:**

#### QUESTION NO: 18

You create a policy-based VPN, and select an address group for the source address.

---

What will be the source component of the proxy-id seen by the remote security gateway?

- A. the default 0.0.0.0/0
- B. the last member of the address group
- C. the first member of the address group
- D. the subnet that contains all addresses in the address group

**Answer: A**

**Explanation:**

#### QUESTION NO: 19

When adding deep inspection to a policy, when will inspection be performed?

- A. before the policy lookup
- B. after the routing lookup
- C. before the destination lookup
- D. after the packet has been permitted

**Answer: D**

**Explanation:**

#### QUESTION NO: 20

When enabling RIP over a hub and spoke VPN, what must you configure on the hub device tunnel interface to allow spokes to receive routing updates?

- A. Point to multipoint
- B. Disable split-horizon
- C. Enable demand circuit
- D. Enable passive interface

**Answer: B**

**Explanation:**

#### QUESTION NO: 21

What is the recommended order of steps to configure inter-VSYS routing?



- A. Create VSYS zones; enter VSYS; configure inter-VR routing; configure VSYS interfaces; create VSYS
- B. Create VSYS; enter VSYS; create VSYS zones; configure VSYS interfaces; configure inter-VR routing
- C. Configure VSYS interfaces; create VSYS; create VSYS zones; enter VSYS; configure inter-VR routing
- D. Create VSYS zones; create VSYS; enter VSYS; configure inter-VR routing; configure VSYS interfaces

**Answer: B**

**Explanation:**

### QUESTION NO: 22

You suspect that there has been an increase in the number of multiple user authentication failures.

In the logs, which severity level would you search to see this event?

- A. Alert
- B. Critical
- C. Warning
- D. Notifications

**Answer: A**

**Explanation:**

### QUESTION NO: 23

Which item in a virtual system is shared by default?

- A. trust zone in the trust-vr
- B. trust zone in the untrust-vr
- C. untrust zone in the trust-vr
- D. untrust zone in the untrust-vr

**Answer: C**

**Explanation:**

**QUESTION NO: 24**

Which two components are required to implement ScreenOS deep inspection? (Choose two.)

- A. policy statements
- B. signature database
- C. IDP action statement
- D. service book group entries

**Answer: A,B**

**Explanation:**

**QUESTION NO: 25**

What is the default number of equal-cost routes that are used by a ScreenOS device?

- A. 1
- B. 2
- C. 3
- D. 4

**Answer: A**

**Explanation:**

**QUESTION NO: 26**

Which two item pairs are exchanged during Phase 2 negotiations? (Choose two.)

- A. proxy-id, SA proposal list
- B. IKE cookie, SA proposal list
- C. hash [ID + Key], DH key exchange
- D. SA proposal list, optional DH key exchange

**Answer: A,D**

**Explanation:**

**QUESTION NO: 27**